Section I. Product Identification and Uses

		HMIS (HFRP) Health Hazard Fire Hazard Reactivity Personal Protectic	3 3 0		
Common / Trade name	ODOR EATER DEODORIZ			TDG	CLASS 3
WHMIS	B2, D1B, D2B			PIN	UN1170 ETHANOL SOLUTION
Code	2000			PG	Ш
Material uses	Liquid deodorant.				
Section II. Hazardous Ingredients Name	CAS#	% by weight	TLV/PEL		LC50/LD50
Ethanol	64-17-5	15 - 40	Not available.		ORAL (LD50): Acute: 7060 mg/kg [Rat.].
Isopropyl alcohol	67-63-0	10 - 30	Not availab	le.	ORAL (LD50): Acute: 3600 mg/kg [Mouse.]. > 4720 mg/kg [Rat].
Methanol	67-56-1	3 - 7	200 mg/m^H3^n STEL: 250 mg/m^H3^n CEIL:		
Alcohol C11 ethoxylate	34398-01-1	1 - 5	Not availab	le.	Not available.

Section III. First Aid Measures

Eye contactIMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. If irritation persists, get medical attention.Skin
contactGently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Cover the irritated skin with an emollient. If irritation persists, seek
medical attention.InhalationAllow the victim to rest in a well ventilated area. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.IngestionINDUCE VOMITING by sticking finger in throat. SEEK IMMEDIATE MEDICAL ATTENTION

Section IV. Physical Data

Cai Data		
Liquid.	Colour	Slightly turbid to colorless.
Not available	Odour	Floral.
Not applicable	Volatility	Not available.
The lowest known value is $65^{\circ}C$ (149°F) (Methyl Alcohol). Weighted average: $88.06^{\circ}C$ (190.5°F)	Vapour density	Weighted average: 1.4 (Air = 1)
0-9-0.91 (Water = 1)	Vapour pressure	The highest known value is 12.9 kPa (97 mm Hg) (at 20°C) (Methyl Alcohol). Weighted average: 4.31 kPa (32.33 mm Hg) (at 20°C)
Easily soluble in cold water, hot water.		
	Liquid. Not available Not applicable The lowest known value is 65°C (149°F) (Methyl Alcohol). Weighted average: 88.06°C (190.5°F) 0-9-0.91 (Water = 1)	Liquid.ColourNot availableOdourNot applicableVolatilityPho lowest known value is 65°C (149°F) (Methyl Alcohol)VolatilityVapour densityVapour density0-9-0.91 (Water = 1)Vapour or pressure

Section V. Fire and Explosion Data			
The product is	Flammable.		
Auto-ignition temperature The lowest known value is 385°C (725°F) (Methyl Alcohol).			
Flash points	Closed cup: 24°C (75.2°F).		
Degradation products	These products are carbon oxides (CO, CO2).		
Extinguising media	Flammable liquid, soluble or dispersed in water. SMALL FIRE: Use DRY chemicals, CO2, alcohol foam or water spray. LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.		

 Section VI. Reactivity Jack Section VI. Reactivity

 Stability
 The product is stable.

 Decomp. products
 Carbon oxides (CO, CO2).

 Reactivity
 Reactive with oxidizing agents, acids.

Section VII. Toxicological properties

2000 ODOR EATER DEODORIZE ...

Route of entry Ingestion. Skin contact. Inhalation. Eye contact.

Toxicity for Acute oral toxicity (LD50): 6200 mg/kg (Rat) (Calculated value for the mixture). Acute toxicity of the gas (LC50): > 5000 ppm (Rat) (Isopropyl alcohol). Acute toxicity of the vapor (LC50): > 5000 ppm (Rat) (Ethanol).

Acute effects Harmful by inhalation, in contact with skin and if swallowed.Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.This product is a eye irritant. This product may irritate skin upon contact.

Chronic CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. The substance (ethanol) is toxic to the reproductive system.

Section VIII. Preventive measure

disposal

Waste Dispose of material according to regional, provincial and federal regulations. Consult your local or regional authorities.

Storage Keep away from heat, from sources of ignition. Keep container tightly closed. Keep in a cool, well-ventilated place. A refrigerated room would be preferable for materials with a flash point lower than 37.8°C (100°F).

Precautions Keep away from heat, from sources of ignition. DO NOT ingest. Do not breathe gas, fumes, vapor or spray. Avoid contact with skin and eyes. Keep out of reach of children. Keep away from incompatibles.

Spill and Eliminate all sources of ignition and ventilate the area. Absorb with an inert material and place in an appropriate waste disposal container. Finish cleaning the spill area with running water. Dispose of in accordance with federal, provincial, or local regulations.

Section IX. Personal protective equipment

Gloves Gloves (impervious).

RespiratorWear appropriate respirator when ventilation is inadequate.EyesSafety glasses.OtherFull suit, apron, face shield, boots: are recommanded under exceptional circumstances such as fire or spill.Eng.Provide exhaust ventilation or other engeneering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Section X. Preparation and other Information

Validated by the Regulatory Affairs Department on 14 apr. 2005

CANUTEC: (613) 996-6666

Printed 5 July 2005

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsability of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Annex A. LegendHMISHazardous Materials Identification SystemWHMISWHMIS Workplace Hazardous Materials Information SystemTDGTransport Dangerous GoodsPINProduct Identification NumberPGPackaging Group